

SPACE TO BE FILLED WITH 6mm THICK EXTERNAL COATING AFTER WELDED 10mm Ø TAPPED HOLE WITH REMOVABLE PLUG FOR AIR TESTING OF JOINT INTERNAL WELD SPACE TO BE FILLED WITH CONCRETE AFTER WELDING EXTERNAL COATING PIPE AXIS 50 75 250 **/**≥ 50 ⋝ 50 F.I.D/2 CONCRETE LINING 4 NOS, 75mm SQ, LUGS WITH 22mm HOLE SPOT WELDED FACILITATE TIGHTENING WITH NUTS AND BOLTS FOR SITE JOINING **EXTERNAL WELD** O.D/2

1050.0

1107.0

554 402

635

10.0 9.5 7.4 7.4 6.5 58 58 58 5

65 60

40

190 180 160 160 160

90

25 20 15 15 5 6 6 6 10 10 5 Ŋ

701.2 628.0 522.7 469.4 415.5 388.4 313.8 257.8 204.0

754.0 667.0 560.3 507.0 453.1 426.0 345.4 286.0 232.2 177.3

377 334 280

45

30 30 25 25 25 25 25 20

45 35 35 35 35 35 25

145

45

60

20 20 20 20 20 20 10 10

145 145

45

145

45 45

45

60 60

40 30

80

213 173

254 227

751.2

804

## DETAILS OF WELDED COLLAR JOINT (FOR PIPE/FITTING 700mm F.I.D. AND ABOVE)

## NOTES-

STATED. MILLIMETRE UNLESS OTHERWISE ALL DIMENSIONS ARE IN

STEEL PIPE BEFORE COATING. 2. THE OUTSIDE DIAMETER OF PIPE SHALL MEAN THE EXTERNAL DIAMETER OF

PIPE F.I.D.

PIPE O.D.

RADIUS (mm)

THICKNESS t

NORMAL 4t+c(mm) ENGAGEMENT

MINIMUM (mm) 4t(mm) B+100

(mm) 4t+2c

70 (mm) 7/90

(mm)

EXTERNAL COATING

⋗

AND BOLTS FOR SITE JOINING

- EXTERNAL WELD

ONCRETE LINING

HEMI- SPHERICAL SLEEVE JOINT

149.1

116

25

20

130 130

30 30 30

STEEL SURFACE SHALL BE PAINTED WITH 2 CRATS OF ENAMEL BEFORE INSTALLATION

145

45

89

4

25

20

130

143

5.8 4.1 4

SURUHANJAYA PERKHIDMATAN AIR NEGARA Area Boweh & Area Satu Prima Avenue, Biok 3510 Jalon Teknokot 6, 83000 Cyber byen Selongor Darul Ehsen, Malaysia

PREPARED BY:

(FOR PIPE/FITTING BELOW 700mm F.I.D.)

DETAILS OF WELDED COLLAR JOINT

PIPE AXIS

F.I.D/2

O.D/2



MINCONSULT SDN. BHD.
No. 6, JALAN 514/223,
46100 PETALING JAVA,
SELANGOR DARUL EHSAN, MALAYSIA.
TELAN TOTAL TELEVISION TO THE TABLE TO TEL. 03-79575757 FAX 03-79547575 / 79547373

DRAWING TITLE:

DETAILS OF JOINTS (SHEET 1 OF 2)

DRAWING NO.

SPAN/WS/STD/F/013